



CRACK SEALANTS MASTICS JOINT SEALANTS ELASTOFLEX NUVO GAP SPECIFICATIONS SEARCH

# ELASTOFLEX 380



- Performance Range
- Suggested Max. Application Temp

ZIP CODE

COMPARE

## RESOURCES

[Print Spec Sheet](#)

[Usage Estimator](#)

[Application Instructions](#)

## DESCRIPTION

Elastoflex 380 is a hot applied, polymer modified asphalt crack sealant. This product applies and sets up best in up to very hot temperatures, and is highly durable in moderate to very hot climates. Elastoflex 380 is fast setting and moderately stiff for parking lot applications. Formulated with a high viscosity to resist excess flow during application, it is ideal for highways, county roads, municipal streets and parking lots. Elastoflex 380 delivers high performance at a moderate cost.

## SPECIFICATION

- Cone Penetration** : 77°F (25°C), 150g, 5s : ASTM D532930 dmm max
- Softening Point** : ASTM D36220°F (104°C) min
- Flow** : 140°F (60°C) : ASTM D53291 mm max
- Resilience** : 77°F (25°C) : ASTM D532925% min
- Viscosity** : 400°F (204°C), Brookfield : ASTM D440210,000 cP max
- Asphalt Compatibility** : 140°F (60°C), 72 hr : ASTM D5329Pass

## APPLICATION

Read and follow application instructions before use. This product must be heated using indirect heating methods, either a double boiler or hot oil circulating kettle. Equipment must have means of maintaining constant agitation to the material.

Maximum safe heating temperature: 400°F (204°C).

Recommended application temperature: 380°F (193°C).

## WARRANTY

Maxwell Products, Inc. warrants that our products meet the applicable specifications at the time of shipment. Due to the many differing procedures used in preparing and installing materials, Maxwell Products assumes no liability for material failure due to improper installation, equipment failure or operator errors. Any remedies are limited, at Maxwell Products' option, to replacement of materials or refund (full or partial) of the purchase price from Maxwell Products. Claims must be made within three (3) months of the date of purchase. There is no other warranty either expressed or implied.



## Products

[Crack Sealants](#)  
[Joint Sealants](#)  
[Mastics](#)  
[Search](#)

## Brands

[Elastoflex](#)  
[Nuvo](#)  
[Gap](#)

## Technology

[Polyskin Packaging](#)  
[Intelibond Technology](#)

## Support

[Contact Us](#)

**NEED TO TALK?**

1-800-266-2090

